

Avalanche (POU Water Cooler)

The Avalanche POU system features double float design and a quick connection inlet to enable easy hook-up to filtration equipment or the water supply. Still boasting its excellent chilling capacity and robust build, this countertop POU is top-of-the-line.



Avalanche: Hot & Cold



Avalanche faucet



LED display



Carrying handle

ITEM		SPECIFICATIONS
Power rating		Single phase 220-240VAC 50Hz
Standard current	220-240VAC	H&C: 2.6A
Power	Cold	74W
Consumption	Hot	450W
Cold	Compressor	Single phase motor
	Refrigerant	R134a
	Capacity	1.7L (0.45 gal)
Hot	Temp control	Bimetal 75-92°C (167-197.6°F)
	Capacity (Internal Heater)	1.5L (0.4 gal)
Refrigerant charge		28.4g (1.0 oz)
Net weight		Hot&Cold: 11.5kg (25.3 lb)
Product boxed weight		Hot&Cold: 13.0 kg (28.7 lb)
Product dimensions		330(W) X 368(D) X 419(H)mm 13.0"(W) X 14.5"(D) X 16.5"(H)
		370(W) x 380(D) x 450(H)mm 14.6"(W) x 15.0"(D) x 17.7"(H)
Loading quantity		20' Container: 450 Units
		40' Container: 960 Units
Certifications		C-UL-US, CE, CB

This Company has a policy of continuous development and reserves the right to change specifications without notification. For further clarifications, please contact us at cmsales@crystalcoolers.com