

Summit (POU Water Cooler)


Elegantly constructed to compliment any décor, be it a salon, kitchen or executive boardroom, the Summit gives "Drinking with Style" a whole new meaning. Specially created Crystal Cloths™ and cleaning solution Crystal Brite™ are perfect for cleaning and shining these stainless steel models.



Summit: Hot & Cold



POU Kit



High grade
Stainless Steel



Hot water "ON"
and "OFF" switch

ITEM		SPECIFICATIONS
Power rating		Single phase (220-240V 50Hz)
Standard current		H&C: 6.2A
Power Consumption	Cold	74W
	Hot	450W
Cold	Compressor	Single phase motor (TS24 LATG)
	Refrigerant	R134a
	Temp range	6°C ± 3°C (43 °F ± 6 °F)
	Temp control	Thermostat (ON - 0°C to 8.9°C ± 1.5°C) (OFF -17.8°C ± 1.5°C)
	Capacity	3.2L (0.84 gal)
Hot	Heater	Band heater
	Temp range	75-92°C (167-197.6°F)
	Safety device	Bimetal (Manual reset 95°C OFF)
	Temp control	Bimetal 84-92 °C (183.2-197.6°F)
	Capacity (External Heater)	2L (0.53 gal)
	Capacity (Internal Heater)	1L (0.26 gal)
Refrigerant charge		28.4g (1.0 oz)
Noise(sound power level)		38dB(A)
Product weight		H&C: 17.5kg (38.6 lb)
Product boxed weight		H&C: 20.4kg (45.0 lb)
Product dimensions		305(W) X 312(D) X 980(H)mm
		12.0"(W) X 12.3"(D) X 38.6"(H)
Product boxed dimensions		375(W) X 400(D) X 1055(H)mm
		14.8"(W) X 15.8 "(D) X 41.5"(H)
Loading quantity		20' Container: 168 Units
		40' Container: 348 Units
Certifications		C-UL-US, CE, CB, CCC, SASO