



## Summit (Hot & Cold)

Elegantly constructed to compliment any décor, be it a salon, kitchen or executive boardroom, the Summit gives "Drinking with Style" a whole new meaning. Specially created Crystal Cloths™ and cleaning solution Crystal Brite™ are perfect for cleaning and shining these stainless steel models.

### General

Available in Cook and or Hot and Cold models, the Summit commands the look of style and elegance for any décor. Complete the classic look with a stainless steel bottle cover and the Summit water dispenser becomes "The Premier Cooler". Crystal Mountain's patented DryGuard™ system is standard on all Summit models offering complete comfort that your water will not end up on the floor due to a faulty bottle. DryGuard™ protects the hardwood floor or the plush boardroom carpet against faulty bottle causing water overflow. Not only will the Summit compliment your surrounding décor, it gives you peace of mind that the water will stay in the reservoir, regardless of the condition of the bottle.



ITEM		SPECIFICATIONS
Power rating		Single phase 220-240VAC 50Hz
Standard current	220-240VAC	H&C: 2.7A
Power Consumption	Cold	74W
	Hot	450W
Cold	Compressor	Single phase motor (TS24 LATG)
	Refrigerant	R134a
	Temp range	6°C ± 3°C (43 °F ± 6 °F)
	Temp control	Thermostat (ON 0°C to 8.9°C ± 1.5°C) (OFF - 17.8°C ± 1.5°C)
	Capacity	2.6L (0.68 gal)
Hot	Heater	Band heater
	Temp range	75-92°C (167-197.6°F )
	Safety device	Bimetal (Manual reset 95°C OFF)
	Temp control	Bimetal 84-92 °C (183.2-197.6°F )
	Capacity (External Heater)	2L (0.53 gal)
	Capacity (Internal Heater)	1L (0.26 gal)
Refrigerant charge		28.4g (1.0 oz)
Noise(sound power level)		38dB (A)
Product weight		H&C: 16.6kg (36.5 lb)
Product boxed weight		H&C: 19.4kg (42.9 lb)
Product dimensions		305(W) X 312(D) X 980(H)mm
		12.0"(W) X 12.3"(D) X 38.6"(H)
Product boxed dimensions		375(W) X 400(D) X 1055(H)mm
		14.8"(W) X 15.8 "(D) X 41.5"(H)
Bottle cover dimensions		305(W) X 312(D) X 145(H)mm
		12.0"(W) X 12.3"(D) X 5.7"(H)
Loading quantity		20' Container: 168 Units
		40' Container: 348 Units
Certifications		C-UL-US, CE, CB, CCC, SASO

