



Crystal Mountain now introduces the Storm point of use water dispenser, following the successful introduction of its counterpart, the Storm Bottom-Load water dispenser.

The Storm point of use water dispenser features an easy to remove reservoir system that takes less than a minute to change. The LED indicator tells you when it needs to be replaced. Servicing has never been easier. With its contemporary design, attractive finish, concealed faucets and easy maintenance, the Storm is sure to dazzle in any environment.

Model: Storm: Hot & Cold



Concealed Water Outlet



Removable Drip Tray



Replaceable Reservoir System
SmartFlo™ Water Cartridge



Unique Sliding Front Door

Specifications:

ITEM		SPECIFICATIONS
Power rating		Single phase 100-115VAC 60Hz
Standard current		Hot & Cold: 4.8~5.3A
Power Consumption	Cold	70W
	Hot	450W
Cold	Compressor	Single phase motor
	Refrigerant	R134a
	Temp range	4-10°C (39.2 - 50°F)
	Temp control	Thermostat (ON 8±1.5°C, OFF 4°C±1.5°C)
	Volume of Cold Reservoir	1.6L (0.4 gal)
Hot	Heater	Internal heater
	Temp range	76-92°C (168.8-197.6°F)
	Safety device	Bimetal (Auto reset: 93 °C OFF)
	Temp control	Bimetal (85°C)(185°F)
	Capacity (Internal Heater)	1.1L (0.3 gal)
Refrigerant charge		30g (1.1 oz)
Noise(sound power level)		Pump: 50dB(A); Compressor: 43dB(A)
Product weight		Hot & Cold: 14.5kg (32.0 lb)
Product boxed weight		Hot & Cold: 16.2kg (35.7 lb)
POU assembly weight		2.0kg (4.5 lb)
POU assembly boxed weight		2.6kg (5.7 lb)
Product dimensions		320(W) x 340(D) x 1116(H)mm 12.6"(W) X 13.4"(D) X 43.9"(H)
Product boxed dimensions		340(W) X 380(D) X 1165(H)mm 13.4" (W) X 15.0" (D) X 45.9" (H)
Loading quantity		20' Container: 204 Units 40' Container: 420 Units
IEC protection class		Class 1
Certifications		C-UL-US, CE, CB